



Calhoun: The NPS Institutional Archive
DSpace Repository

Theses and Dissertations

1. Thesis and Dissertation Collection, all items

1965

Computer investigation of low energy neutron-neutron scattering

Osgood, Franklin Baker

Monterey, California: U.S. Naval Postgraduate School

<http://hdl.handle.net/10945/11835>

This publication is a work of the U.S. Government as defined in Title 17, United States Code, Section 101. Copyright protection is not available for this work in the United States.

Downloaded from NPS Archive: Calhoun



<http://www.nps.edu/library>

Calhoun is the Naval Postgraduate School's public access digital repository for research materials and institutional publications created by the NPS community. Calhoun is named for Professor of Mathematics Guy K. Calhoun, NPS's first appointed -- and published -- scholarly author.

Dudley Knox Library / Naval Postgraduate School
411 Dyer Road / 1 University Circle
Monterey, California USA 93943

NPS ARCHIVE
1965
OSGOOD, F.

COMPUTER INVESTIGATION OF LOW ENERGY
NEUTRON-NEUTRON SCATTERING

FRANKLIN B. OSGOOD

1944
JANUARY 10 - MONTESSORI SCHOOL
MONTREAL, CANADA

COMPUTER INVESTIGATION
OF LOW ENERGY
NEUTRON-NEUTRON SCATTERING

* * * * *

Franklin B. Osgood

COMPUTER INVESTIGATION
OF LOW ENERGY
NEUTRON-NEUTRON SCATTERING

by

Franklin B. Osgood
Lieutenant, United States Navy

Submitted in partial fulfillment of
the requirements for the degree of

MASTER OF SCIENCE

IN

PHYSICS

United States Naval Postgraduate School

Monterey, California

1 9 6 5

965

OSGOOD, F.

COMPUTER INVESTIGATION
OF LOW ENERGY
NEUTRON-NEUTRON SCATTERING

by

Franklin B. Osgood

This work is accepted as fulfilling the
thesis requirements for the degree of

MASTER OF SCIENCE

IN

PHYSICS

from the

United States Naval Postgraduate School

ABSTRACT

A proposed neutron-neutron scattering experiment in which the neutron source would be colliding beams from an underground nuclear explosion, was investigated. In particular, the accuracy to be expected was determined so as to allow evaluation of the worth of the experiment. Phase shift analysis was performed for Gaussian, Exponential, Yukawa, and Square Well spherically symmetric potentials. The energy range considered was 20 kev to 2.6 MeV. Scattering length was found to be determined to within 6% and effective range within 40% for a 10% scattering cross section accuracy. Potential depth would be determined to at least .5% and range to .3%.

TABLE OF CONTENTS

Section	Title	Page
1.	Introduction	1
2.	Possible Dineutron State	4
3.	Effective Range and Potential Parameters	5
4.	Phase Shift Analysis	27
5.	Shape Independent Approximation	50
6.	Summary	53
	Acknowledgement	55
Appendix		
I.	Computer Program Description	56
II.	Program Dictionary	58
III.	Program Listing	61
IV.	Sample Results	90
	Bibliography	101

LIST OF GRAPHS AND TABLES

Graph		Page
1. - 4.	Potential Depth as Function of Scattering Length for Square, Gaussian, Exponential, and Yukawa Wells	11-14
5. - 8.	Potential Radius as Function of Scattering Length for Square, Gaussian, Exponential, and Yukawa Wells	15-18
9. - 12.	Potential Depth as Function of Effective Range for Square, Gaussian, Exponential, and Yukawa Wells	19-22
13. - 16.	Potential Radius as Function of Effective Range for Square, Gaussian, Exponential, and Yukawa Wells	13-26
17.	Total Cross Section as Function of Energy for Various Scattering Lengths, Gaussian Potential	34
18. - 28.	Normalized Cross Section as Function of Energy for Various Scattering Lengths: Square Well, Gaussian, Exponential, and Yukawa Potentials	36-46
29. - 31.	Normalized Cross Section as Function of Energy for Various Effective Ranges: Gaussian, Exponential, and Yukawa Potentials	47-49
32. - 33.	Comparison of Total Cross Sections as a Function of Energy for Effective Range Theory; Square Well, Gaussian, Exponential, and Yukawa Potentials	51-52

TABLE

I.	Effect of Changes in Scattering Length upon Potential Parameters	8
II.	Effect of Changes in Effective Range upon Potential Parameters	9
III.	Percentage Change in Potential Parameters Caused by a Ten Percent Change in Scattering Length and Effective Range	10

IV.	Effect of a Ten Percent Error in Total Cross Section upon the Error in Scattering Length	32
V.	Effect of a Ten Percent Error in Total Cross Section upon the Error in Effective Range	33

1. Introduction

A low energy neutron-neutron scattering experiment utilizing a single underground nuclear explosion has been proposed and studied. [2,3] Preliminary studies indicate the scattering cross section might be measured to an accuracy of 10% from 20 keV to 2 MeV. The efforts of this paper are directed to a numerical investigation of the expected scattering with special attention given to: (a) the possible existence of the dineutron; (b) the effect of changes in effective range and scattering length upon the range and depth of the spherically symmetric Gaussian, Exponential, Yukawa, and Square Well Potentials; (c) the effect of changes in effective range and scattering length upon the scattering cross section from each of the potential shapes in (b); and (d) a comparison of calculated cross sections from the four potential shapes in (b) with the shape-independent cross section.

Precise determination of the neutron-neutron scattering parameters would be important for a number of reasons as stated by Moravcsik. [3] These reasons include: (1) an investigation of charge independence; (2) an investigation of charge symmetry; and (3) the existence or non-existence of a slightly unbound dineutron resonance state.

This investigation attempted to locate a dineutron state in section 2 to provide a theoretical justification for its experimental quest. In Sections 3 and 4, 2 to 16% deviations in the ratio of effective range to scattering length from the accepted n-p ratio were investigated for their effect on scattering cross sections and Gaussian, Exponential, Yukawa, and Square Well Potential parameters. These results should allow some determination of the accuracy in experimental results required to determine to a given accuracy the shape-independent scattering parameters.

In Section 5, the cross section from effective-range theory is compared with cross sections from potential scattering to test the validity of the shape independent approximation. This report concludes with a summary in section 6 and the complete computer program used in the calculations along with the calculation results as a part of the appendix.

The analysis was performed using phase shift scattering methods. The well established scattering length and effective range for neutron-proton scattering, a_s^* and $r_{0,s}^*$, were taken as a base for calculations. The ratio of effective range to scattering length was formed to yield a spherically symmetric potential range and depth for square well, exponential, gaussian, and yukawa potentials. The absolute value of the scattering length was then varied in 2% steps up to 16% while holding the effective range constant at its accepted value. 17 sets of potential parameters were thus obtained for each of the four potential shapes. Then, using the maximum and minimum acceptable value of effective range as a base, the effective range was varied in 2% increments up to 6% while holding the scattering length constant at its accepted value. Eight additional sets of potential parameters were obtained for each of the potential shapes.

The spherically symmetric radial wave equation was then numerically integrated using a fourth order runge kutta method for all calculated sets of parameters and potential shapes. Integration was performed for 30 values of center of mass energy ranging from 20 kev to 2.6MeV and was carried out to a radius at which the effect of the nuclear potential was no longer felt.

The logarithmic derivative of the numerically integrated solution was then compared to the logarithmic derivative of the exact field-free asymptotic solution outside the range of the nuclear potential and a

phase shift obtained.

The total cross section as a function of center of mass energy was then calculated from the phase shift for each case. A ratio of each cross section to that obtained from the accepted neutron-proton scattering potential parameters was formed. This gave the per cent change in total cross section for each incremental change in scattering length and effective range.

Per cent change in total cross section from that for n-p scattering parameter calculations was plotted against energy for significant increments in two different energy ranges, 20 kev to 100 kev and 100 kev to 2.6MeV. Potential depth and range were plotted against the ratio of effective range to scattering length for each potential shape. A comparison of shape-independent effective range scattering calculations with potential scattering calculations was made by plotting the total cross section for each case on the same graph.

2. Possible dineutron state

An attempt was made to justify the possible existence of a dineutron resonance state near zero energy using a compound nucleus model, but failure was met in attempting to formulate a compound nucleus model for neutron-neutron scattering.

Numerical calculations for neutron-neutron potential scattering were made for a large number of potential depths on the Control Data Corporation 1604 digital computer in an attempt to find possible resonances, particularly a sharp resonance. Gaussian, exponential, and yukawa potentials were used with potential depths ranging from 0 to the value obtained from the accepted n-p scattering parameters in 2.5 MeV steps over two center of mass energy ranges, 20 to 100 kev and .1 to 2.6 MeV. Results were scanned for resonances. No resonances were expected and none were found.

3. Effective range and potential parameters

Detailed comparisons with experiments have given for the singlet effective range and scattering length for neutron-proton scattering:

$$r_{o,s}^* = 2.46 \pm 0.12 \text{ FM} \quad a_s^* = -23.677 \pm 0.029 \text{ FM} \quad [4]$$

For an examination of the effect of deviations from this scattering length on the scattering cross section, the ratio $r_{o,s} / a_s$ was formed and a_s was varied in magnitude from 0-16% in 2% steps while holding $r_{o,s}$ at its accepted value, 2.46 Fm. To examine the effect of deviations in effective range on the scattering cross section, the ratio $r_{o,s} / a_s$ was again formed using the accepted value for a_s , -23.677 Fm, and the maximum and minimum values for $r_{o,s}$, 2.58 Fm and 2.34 Fm respectively. $r_{o,s}$ was varied up to 6% in 2% steps in the direction of increasing deviation from the accepted value, 2.46 Fm.

Four spherically symmetric potential shapes were then examined. These potentials are:

$$\begin{aligned} \text{Square Well:} \quad V &= -V_0 & r \leq r_n \\ V &= 0 & r > r_n \end{aligned}$$

$$\begin{aligned} \text{Gaussian Well:} \\ V &= -V_0 \exp [-(r/r_n)^2] \end{aligned}$$

$$\begin{aligned} \text{Yukawa Well:} \\ V &= -V_0 \frac{\exp [-r/r_n]}{r/r_n} \end{aligned}$$

$$\begin{aligned} \text{Exponential Well:} \\ V &= -V_0 \exp [-r/r_n] \end{aligned}$$

Blatt and Jackson have arrived at a correspondence between the ratio of effective range to scattering length and the potential parameters, V_0 and r_n , for each of the well shapes investigated. [1] The well parameters are given in terms of the intrinsic range, b , and the well depth parameter, S . The well depth, $V(r)$, for the potential in question is multiplied by a constant such that the first resonance occurs at zero energy. The well depth parameter is then the inverse of this constant given by:

$$V(r) = S V_{\text{RES}}(r)$$

The intrinsic range, b , is determined by the shape and range of the adjusted potential through the radial wave function for that potential. It is defined by:

$$b \equiv r_{0_{\text{RES}}} = 2 \int_0^x [1 - u_{0_{\text{RES}}}^2(r)] dr$$

Blatt and Jackson provide interpolation formulas to relate V_0 and r_n to r_0 and a . The form of their formulas have been changed slightly to fit the definition of the potentials in this report. In their modified form, these interpolation formulas are:

Square Well:

$$S = [1 - 1.574(r_0/a) + .353(r_0/a)^2] / [1 - 2.384(r_0/a) + 1.90(r_0/a)^2]$$

$$b = r_0 / [1 - .500(S-1) + .486(S-1)^2 - .476(S-1)^3 + .378(S-1)^4 - .158(S-1)^5]$$

$$V_0 = 1.02276 \times 10^{-24} S / b^2$$

$$r_n = b$$

Gaussian Well:

$$S = [1 - 2.030(r_0/a) + .587(r_0/a)^2] / [1 - 2.810(r_0/a) + 1.805(r_0/a)^2]$$

$$b = r_0 / [1 - .641(S-1) + .568(S-1)^2 - .721(S-1)^3 + 1.172(S-1)^4 - 1.015(S-1)^5]$$

$$V_0 = 2.29208 \times 10^{-24} S / b^2$$

$$r_n = [b^2 / 2.0604]^{1/2}$$

Exponential Well:

$$s = [1 - 2.9739(r_0/a) + 1.3602(r_0/a)^2] / [1 - 3.7134(r_0/a) + 3.1177(r_0/a)^2]$$

$$b = r_0 / [1 - .904(s-1) + .745(s-1)^2 - .543(s-1)^3 + .174(s-1)^4]$$

$$V_0 = 7.51541 \times 10^{-24} s / b^2$$

$$r_n = b / 3.5412$$

Yukawa Well:

$$s = [1 - 3.5093(r_0/a) + 2.0354(r_0/a)^2] / [1 - 4.1348(r_0/a) + 3.7072(r_0/a)^2]$$

$$b = r_0 / [1 - 1.369(s-1) + 1.093(s-1)^2 - 1.127(s-1)^3 + 1.005(s-1)^4 - .324(s-1)^5]$$

$$V_0 = 3.12821166 \times 10^{-24} s / b^2$$

$$r_n = b / 2.1196$$

The results of these calculations are presented both in tabular and in graphical form in tables I and II and in graphs 1 through 16. The tables are arranged to exhibit V_0 and r_n as a function of the percentage deviation of r_0 and a from $r_{0,s}^*$ and a_s^* , the best values from n-p scattering. The graphs depict V_0 and r_n as a function of r_0/a using the left and bottom scales respectively. Using the top and right scales, the percentage deviation of V_0 and r_n from the best n-p scattering parameters is shown as a function of the percentage deviation of r_0/a from $r_{0,s}^*$ and a_s^* .

Variations in potential parameters were found to be of the order of a .5% increase in $|V_0|$ and a .5% decrease in r_n for a 10% increase in scattering length. A 10% increase in effective range, however, was observed to cause a decrease in $|V_0|$ of approximately 8% while increasing r_n about 9%. This data is shown in table III.

TABLE 1
EFFECT OF CHANGES IN SCATTERING LENGTH UPON POTENTIAL PARAMETERS

$r_0 = 2.46 \text{ Fm}$					
%Change in a^*	r_0/a	SQUARE WELL		GAUSSIAN WELL	
		$-V_0$	r_n	$-V_0$	r_n
-16	-.087275	16.92	2.379	38.58	1.645
-14	-.089353	16.92	2.377	38.59	1.644
-12	-.091431	16.92	2.375	38.61	1.642
-10	-.093508	16.92	2.373	38.62	1.641
-8	-.095586	16.92	2.372	38.64	1.639
-6	-.097664	16.92	2.370	38.66	1.638
-4	-.099742	16.92	2.368	38.67	1.636
-2	-.101820	16.92	2.366	38.69	1.635
0	-.103898	16.92	2.365	38.70	1.633
2	-.105976	16.92	2.363	38.72	1.632
4	-.108054	16.92	2.361	38.74	1.630
6	-.110132	16.93	2.359	38.75	1.629
8	-.112210	16.93	2.358	38.77	1.628
10	-.114288	16.93	2.356	38.78	1.626
12	-.116366	16.93	2.354	38.80	1.625
14	-.118444	16.93	2.352	38.82	1.623
16	-.120522	16.93	2.351	38.83	1.622
		EXPONENTIAL WELL		YUKAWA WELL	
		$-V_0$	r_n	$-V_0$	r_n
		130.2	.6585	56.21	1.086
		130.3	.6578	56.31	1.084
		130.5	.6570	56.41	1.083
		130.6	.6563	56.51	1.081
		130.7	.6555	56.61	1.080
		130.9	.6548	56.71	1.078
		131.0	.6540	56.80	1.077
		131.1	.6533	56.90	1.075
		131.2	.6525	57.00	1.074
		131.4	.6518	57.09	1.072
		131.5	.6511	57.19	1.071
		131.6	.6503	57.29	1.069
		131.8	.6496	57.38	1.068
		131.9	.6489	57.48	1.066
		132.0	.6482	57.57	1.065
		132.1	.6475	57.67	1.064
		132.3	.6468	57.76	1.062

TABLE II

EFFECT OF CHANGES IN EFFECTIVE RANGE UPON POTENTIAL PARAMETERS


$$a_s = -23.677$$

%Change in r_0	r_0/a	SQUARE WELL		GAUSSIAN WELL		EXPONENTIAL WELL		YUKAWA WELL	
		$-V_0$	r_n	$-V_0$	r_n	$-V_0$	r_n	$-V_0$	r_n
60	-.166237	6.622	3.703	15.30	2.547	52.71	1.011	23.24	1.653
40	-.145458	8.644	3.263	19.91	2.247	68.24	.8939	30.03	1.464
20	-.124678	11.76	2.817	26.99	1.943	92.02	.7744	40.24	1.271
10	-.114288			32.05	1.789	109.0	.7138		
8.88	-.113325	14.23	2.571			110.8	.7081	48.28	1.164
6.88	-.111146	14.79	2.523			115.1	.6953	50.10	1.143
4.88	-.108967	15.39	2.475			119.6	.6825	52.03	1.122
0	-.103893	16.92	2.365			131.2	.6525	57.00	1.074
-4.88	-.098830	18.7	2.253			144.7	.6224	62.73	1.025
-6.88	-.096853	19.47	2.210			150.5	.6106	65.21	1.005
-8.88	-.094877	20.29	2.166			156.7	.5988	67.85	.983
-10	-.093509			47.68	1.477	161.2	.5906		
-20	-.083119	26.43	1.906	60.22	1.319	203.0	.5281	37.5	.8710
-40	-.062339	46.97	1.441	106.6	.9982	35.71	.4008	152.8	.6629
-60	.041560	105.7	.9680	238.8	.6719	794.8	.2706	337.1	.4489


TABLE III


PERCENTAGE CHANGE IN WELL PARAMETERS CAUSED BY A TEN PERCENT INCREASE
IN SCATTERING LENGTH AND EFFECTIVE RANGE

	<u>10% increase in a</u> <u>% increase in</u>		<u>10% increase in r_0</u> <u>% increase in</u>	
	$ V_0 $	r_n	$ V_0 $	r_n
SQUARE WELL	.1	-.4	-8	10
GAUSSIAN WELL	.2	-.5	-8	9
EXPONENTIAL WELL	.5	-.6	-8	9
YUKAWA WELL	.8	-.5	-8	9




GRAPH 1






GRAPH. 3



GRAPH 4



GRAPH 5

EXPONENTIAL RADIUS, r_e (FM)

.660

.655

.650

.645

-12

-11

r_0/a

-10

-09

-08

GRAPH 6

CHANGE IN $|Q|$ (%)

-16

-12

-8

-4

0

+4

+8

+12

+16

EXPONENTIAL RANGE

VS

RATIO OF EFFECTIVE RANGE
TO SCATTERING LENGTH
FOR VARYING SCATTERING
LENGTH. $r_0 = 2.46$ FM

1.0

.5

0


-.5

-1.0


CHANGE IN r_e (%)

r_0^*/a_s^*


YUKAWA WELL DEPTH, $|V_0|$ (MEV)




GRAPH 7




GRAPH 8







GRAPH 10




GRAPH 11




GRAPH 12




GRAPH 13



GRAPH 14



GRAPH 15



GRAPH 16

4. Phase shift analysis

A partial wave analysis of neutron-neutron scattering was performed for all potential parameters calculated in section 3.

Assuming a spherically symmetric potential, the radial wave equation

$$\frac{1}{r^2} \frac{d}{dr} \left(r^2 \frac{dR}{dr} \right) + \left\{ \frac{2m}{\hbar^2} [E - V(r)] - \frac{\lambda}{r^2} \right\} R = 0 \quad (1)$$

becomes

$$-\frac{\hbar^2}{2m} \frac{d^2 U}{dr^2} + \left[V(r) + \frac{\lambda(\lambda+1)\hbar^2}{2m r^2} \right] U = E U \quad (2)$$

where $U(r) = r R(r)$

Rearranging, equation (2) becomes

$$\frac{d^2 U}{dr^2} = - \left\{ k^2 - V'(r) - \frac{\lambda(\lambda+1)}{r^2} \right\} U \quad (3)$$

where $k^2 = ME/\hbar^2 = [E(\text{MEV})/41.499] \times 10^{26}$

and $V'(r) = MV(r)/\hbar^2 = [V(r)(\text{MEV})/41.499] \times 10^{26} \quad [6]$

M = neutron-proton reduced mass

E = center of mass energy = 1/2 laboratory energy

Separating equation (3) into two first order equations for simultaneous numerical integration gives

$$Z = \frac{dU}{dr} \quad (4)$$

$$\frac{dZ}{dr} = - \left\{ k^2 - V'(r) - \frac{\lambda(\lambda+1)}{r^2} \right\} U \quad (5)$$

Equations (4) and (5) were numerically integrated using a fourth order Runge-Kutta method with Boundary conditions:

For $r = 0$

$$U(0) = 0$$

$$Z(0) = 1$$

Integration was carried outside the range of the nuclear potentials with 500 to 750 steps to about 15 fm for two center of mass energy ranges; 0-100 kev in 20 kev intervals, and .1-2.6 MeV in .1 MeV intervals. The values of Z and U at $r = 15$ fm are referred to as Z_n and U_n .

The exact asymptotic solution of the field-free wave equation, equation (1) with $V' = 0$, is given by Zeleny as: [7]

$$R_l(r) = A_l \{ \cos \delta_l j_l(kr) - \sin \delta_l n_l(kr) \} \quad (6)$$

from which

$$\frac{dR_l}{dr} = A_l \left\{ \cos \delta_l \left[-\frac{k}{2l+1} (l j_{l-1}(kr) - (l+1) j_{l+1}(kr)) \right] - \sin \delta_l \left[-\frac{k}{2l+1} (l n_{l-1}(kr) - (l+1) n_{l+1}(kr)) \right] \right\} \quad (7)$$

With the substitutions

$$U_l = r R_l$$

$$\frac{dU_l}{dr} = r \frac{dR_l}{dr} + R_l$$

equations (6) and (7) become:

$$U_l(r) = A_l r \{ \cos \delta_l j_l(kr) - \sin \delta_l n_l(kr) \} \quad (8)$$

$$\begin{aligned} \frac{dU_l(r)}{dr} = A_l \{ r \left[\frac{k}{2l+1} \cos \delta_l (l j_{l-1}(kr) - (l+1) j_{l+1}(kr)) \right. \\ \left. - \frac{k}{2l+1} \sin \delta_l (l n_{l-1}(kr) - (l+1) n_{l+1}(kr)) \right] \} \end{aligned} \quad (9)$$

where δ_l is the scattering phase shift and j_l and n_l are spherical Bessel and Neuman functions respectively.

The scattering phase shift, δ_l , is obtained by matching the logarithmic deviations of the exact field-free and numerical solutions at a range where the nuclear force is negligible. This procedure yields;

For $\lambda = 0$

$$\left. \frac{Z_n}{u_n} \right|_{r=15 \text{ FM}} = \{ r [k n_1(kr) \sin \delta_0 - k j_1(kr) \cos \delta_0] + j_0(kr) \cos \delta_0 - n_0(kr) \sin \delta_0 \} / \{ r [j_0(kr) \cos \delta_0 - n_0(kr) \sin \delta_0] \} \Big|_{r=15 \text{ FM}}$$

For $\lambda = 1$

$$\left. \frac{Z_n}{u_n} \right|_{r=15 \text{ FM}} = \{ r \left[\frac{k}{3} \cos \delta_1 (j_0(kr) - 2j_2(kr)) - \frac{k}{3} \sin \delta_1 (n_0(kr) - 2n_2(kr)) \right] + \cos \delta_1 j_1(kr) - \sin \delta_1 n_1(kr) \} / \{ r [\cos \delta_1 j_1(kr) - \sin \delta_1 n_1(kr)] \} \Big|_{r=15 \text{ FM}}$$

Rearranging and taking the inverse tangent we get the following expressions for the phase shift:

$$\delta_0 = \tan^{-1} \left\{ \frac{\left[\frac{Z_n}{u_n} j_0(kr) + k j_1(kr) \right] r - j_0(kr)}{\left[\frac{Z_n}{u_n} n_0(kr) + k n_1(kr) \right] r - n_0(kr)} \right\} \quad (10)$$

$$\delta_1 = \tan^{-1} \left\{ \frac{\left[\frac{k}{3} j_0(kr) - \frac{2k}{3} j_2(kr) - \frac{Z_n}{u_n} j_1(kr) \right] r + j_1(kr)}{\left[\frac{k}{3} n_0(kr) - \frac{2k}{3} n_2(kr) - \frac{Z_n}{u_n} n_1(kr) \right] r + n_1(kr)} \right\} \quad (11)$$

The total cross section as a function of energy is obtained from the phase shift using the relation [8]

$$\sigma(E) = \sum_l \frac{4\pi}{k^2} (2l+1) \sin^2 \delta_l \quad (12)$$

For identical particle scattering, equation (12) becomes, for the singlet state:

$$\sigma_s(E) = \sum_{\text{even}} \frac{4\pi}{k^2} (2l+1) \sin^2 \delta_l$$

and for the triplet state:

$$\sigma_t(E) = \sum_{\text{odd}} \frac{4\pi}{k^2} (2l+1) \sin^2 \delta_l$$

The computation of cross sections was made for both the singlet $l = 0$ state and the triplet $l = 1$ state. The $l = 1$ cross sections were observed to be at least 3 orders of magnitude smaller in the energy range under consideration and were disregarded in subsequent computations. The computer program in appendix III however, retains the capability of $l = 1$ calculations.

The computer program in appendix III was used in cross section calculations for all the potential parameters in section 3. First the program computed the potential parameters at the base scattering length and effective range and at percentage deviations from this base read into it in its input section. The total scattering cross section was then computed as a function of center of mass energy. The calculated cross section for each set of potential parameters was then divided by the cross section for the base parameters to normalize the cross section and present it as a deviation from the base.

The resulting data was plotted to show the percentage difference in total cross section from the calculated total cross section for n-p scattering with $a_s^* = -23.677$ fm and $r_{0,s}^* = 2.46$ fm as a function of energy for percentage deviations of a and r_0 . The graphs are drawn over two distinct energy ranges, 20 - 100 kev and .1-2.6 MeV, to better portray results and separate graphs are provided for each

potential shape.

In Moravcsik's paper, the function $Q(T)$ is defined by:

$$Q(T) \equiv \left(\frac{d\sigma}{d\Omega} \right)^{-1} = \frac{1}{a^2} + \left(1 - \frac{r_0}{a} \right) \epsilon = 4\pi / \sigma(E)$$

where $\epsilon = \frac{MT}{2}$ for T = laboratory kinetic energy and m = neutron mass.

Moravcsik has determined that in a 10% experiment, a linear approximation for $Q(T)$ would be sufficient.

The value of this straight line at $\epsilon = 0$ would give $1/a^2$ directly while the slope of the straight line would determine r_0/a and the sign of a .

Moravcsik concludes that a determination of total cross section to 10% accuracy at ten suitably distributed energy points could determine the scattering length to 3% and the effective range to 50 - 70%.

Tables IV, V of this report show that a 10% determination of total cross section in the vicinity of the n-p scattering parameters will allow a 6% determination of a_s at 20 kev and a 16% determination at 400 kev while at 2.6 MeV a 16% error in scattering length has only a 2% effect on total cross section. The same tables show that a 10% determination of total cross section will allow a 40% determination in effective range at 2.6 MeV while a 100% error in effective range has approximately a 2% effect at 20 kev.

An alternate method of determining the effective range parameters is therefore offered. The magnitude of the total cross section at 20 kev could be compared to supplemented data of this report to arrive at a value for a_s within 6%. Graph 17 is shown as an illustration of possible supplemental data. The magnitude of the total cross section at 2 MeV or greater could, in the same manner, be used to arrive at a

TABLE IV


EFFECT OF A 10% ERROR IN TOTAL CROSS SECTION UPON THE ERROR IN a_s % Error in a_s for

ENERGY (kev)	SQUARE WELL	GAUSSIAN	EXPONENTIAL	YUKAWA
20	8-16	6	6	6.5
60	8-16	8.5	8.5	9.5
100	8-16	11	12	16
200	8-16	16.5	16.5	18

TABLE V

EFFECT OF A 10% ERROR IN TOTAL CROSS SECTIONS UPON THE ERROR IN r_0 %error in $r_{0,s}$ for


ENERGY (MeV)	GAUSSIAN	EXPONENTIAL	YUKAWA
1.6	60	58	62
1.8	56	52	59
2.0	53	50	57
2.2	50	47	55
2.4	45	45	52
2.6	40	42	50



GRAPH 17

value for $r_{0,s}$ within 50%. Because of the negligible effect of both large errors in $r_{0,s}$ at the low energy cross section and large errors in a_s at the high energy cross section, they may be determined independently, each having little effect upon the determination of the other. Either gaussian, exponential, or yukawa data could be used because of only about a 1% difference in a_s value among them for any given cross section. Thus the scattering length and effective range could be determined with a minimum of two points, one at either end of the energy range. For greater accuracy, the computer program in the appendix could easily be adapted to a searching interpolation. An advantage could be gained if the necessity for only two values of cross section would allow a more precise determination of those two values. It can be seen from accompanying graphs that the energy must be accurate to 10% to achieve meaningful results in this way. If this energy accuracy is not feasible, then the method outlined by Moravcsik for scattering length and effective range determination must be used. In any event, Moravcsik's development of expected accuracies is confirmed by this phase shift analysis.

NORMALIZED TOTAL CROSS SECTION
VS
CENTER OF MASS ENERGY
SQUARE WELL



GRAPH 18

NORMALIZED CROSS SECTION
VS
CENTER OF MASS ENERGY
SQUARE WELL
 $\Gamma_0 = \Gamma_{0,s}^*$

DIFFERENCE IN TOTAL CROSS SECTION (%)

15

10

5

0

.5

1.0

1.5


2.0

2.5


E (MEV)


$\alpha = 108\% \alpha_s^* \pm 0.116\% \alpha_s^*$

GRAPH 19




GRAPH 20





GRAPH 22



GRAPH 23

NORMALIZED CROSS SECTION
VS
CENTER OF MASS ENERGY
EXPONENTIAL WELL
 $\Gamma_0 = \Gamma_{0,s}^*$

DIFFERENCE IN TOTAL CROSS SECTION (%)

25

20

15

10

$Q = 116\% Q_s^*$

$114\% Q_s^*$

$112\% Q_s^*$

$110\% Q_s^*$

$E(\text{KEV})$

120

100


80

60


40

20


0




GRAPH 25




GRAPH 26







GRAPH 28



GRAPH 29



GRAPH 30



GRAPH 31

5. Shape independent approximation

The total cross section for neutron-neutron scattering was calculated by the shape independent approximation of effective range scattering theory using $r_{0,s}^*$ and a_s^* . This cross section was compared with that from the potential scattering calculations in section 4.

Segré¹ gives for the total cross section

$$\sigma(E) = \frac{4\pi}{k^2} \frac{1}{1 + \cot^2 \delta_0} = \frac{4\pi}{k^2 + \frac{1}{a(k)^2}}$$

where $a(k)$ is the scattering length as a function of wave number. An approximation for $a(k)$ is given for $k \neq 0$ as:


$$1/a(k) = -k \cot \delta_0 = \frac{1}{a(0)} - \frac{1}{2} r_0 k^2 + \dots$$


which, when substituted for $a(k)$ in the cross section formula yields:

$$\sigma(E) = \frac{4\pi}{k^2 + \left(\frac{1}{a} - \frac{r_0 k^2}{2}\right)^2} \quad (1a)$$

Formula (1a) was used in a calculation of total cross section in the energy range .1 - 2.6 MeV and compared with the cross sections obtained from potential scattering for the same parameters. The results are shown in graphs 32 - 33.

The results of the effective range theory calculations compare favorably with potential scattering calculations. A 2% difference is the greatest deviation noted in the comparison. This confirms the commonly held belief that the shape independent approximation of effective range theory is quite accurate in this energy range.





GRAPH 33

6. Summary

In section 4 it was determined that a 10% scattering experiment could define a scattering length to approximately 6% and an effective range to approximately 40% accuracy. This accuracy might be achieved with only two values of cross section; that at 20 kev and that at 2.6 MeV, if the energy could be determined to 10% in both regions. Certainly it would be achieved by a least squares fit at 10 - 20 appropriately distributed energies as proposed by Moravcsik.

In the region of the accepted n-p scattering length and effective range, it was found that a 2% change in scattering length resulted in a 3.1% change in cross section at 20 kev center of mass energy while only causing a .1% change in total cross section at 2.6MeV. A 20% change in effective range was seen to cause a 5% change in cross section at 2.6MeV while having almost no effect at 20 kev. Thus the conclusion was reached that effective range and scattering length could be determined separately and independently by the cross sections at the high and low ends of the proposed energy range.

In section 3 it was found that a 1% change in potential depth or range resulted in about a 20% change in scattering length and about a 1% change in effective range for Exponential and Gaussian wells.

For the Yukawa well, a 1% change in potential depth and range resulted in about a 12% change in scattering length and a 1% change in effective range.

It was conversely determined that a 6% determination of scattering length can determine the Gaussian and Exponential potential depths to less than - .2% and the potential range to less than - .3% for the n-p scattering length and effective range vicinity. The Yukawa well

depth would be determined to less than $-.5\%$ and the potential range to $-.2\%$.

It therefore seems quite likely that a 10% scattering experiment would determine the scattering length and effective range accurately enough to furnish an acceptable set of potential parameters. These potential parameters appear to be adequate to investigate charge - independent and charge-symmetry effects.

Effective range theory was quite adequate to determine cross sections in the examined energy range. A 1% agreement was found with potential scattering. There should be little question of its propriety here.

ACKNOWLEDGMENT

The patient aid and excellent counsel provided by Professor E. B. Buskirk is gratefully acknowledged and greatly appreciated.

APPENDIX 1

COMPUTER PROGRAM DESCRIPTION

The program is written in FORTRAN II language and, as listed in Appendix III, is arranged to operate with the Control Data Corporation-1604 as a central processor and the I B M - 1401 as peripheral equipment. The library tape functions used are the standard FORTRAN II functions with the exception of a subroutine called DRAW. This subroutine is a part of the library tape at the Computer Center of the United States Naval Postgraduate School and is identified by its large computer operators co-op ID: J7-NPS-DRAW. The subroutine was written by J.R. Ward of the U.S. Naval Postgraduate School. Where this subroutine is not available, the program can be run by omitting subroutines SKETCH and NOW and their call cards.

The program consists of a main routine and 13 subroutines. The main routine calls the subroutines in proper sequence and also provides for a sequential variation of the parameters r_n , and V_0 . The subroutines and the function each performs are listed as follows:

Subroutine INPUT2	Reads in data cards
Subroutine READY2	Calculates and tabulates energies, wave numbers, scattering lengths, effective ranges, potential parameters, and calls bessel functions.
Subroutine FIGURE	Prepares for and calls integration routine, forms the logarithmic derivative of the integrated function.
Subroutine RKUTTA	Integrates equation provided by DERIV for $\lambda = 0$.
Subroutine RKUTTA1	Integrates equation provided by DERIV1 for $\lambda = 1$.
Subroutine DERIV	Provides $\lambda = 0$ equation for integration for a particular potential.

Subroutine DERIV1	Provides $l = 1$ equation for integration for a particular potential.
Subroutine FINISH	Computes phase shifts, cross sections, and normalized cross sections.
Subroutine OUTPUT	Prints out resulting r_0/a ratio, V_0 , r_n , energy, phase shifts, and cross sections.
Subroutine BESSEL	Calculates besse1 functions
Subroutine SKETCH	Prepares for and calls DRAW to plot all cross sections on one graph for comparison.
Subroutine APPEND	Stores base cross section for normalization in FINISH.
Subroutine NOW	Prepares for and calls DRAW to plot all normalized cross sections on one graph for comparison.

APPENDIX II

PROGRAM DICTIONARY

EINT	Initial value of center of mass energy in MeV.
EINC	Incremental value of center of mass energy in MeV.
II	Maximum number of center of mass energy values.
ROS	Base effective range in cm.
AS	Base scattering length in cm.
CHANGE	Percentage incremental change in base effective range or base scattering length in decimal form.
MANY	Number of + or - incremental charges to be made.
REND	Radius at which integrated solution is matched to exact solution for phase shift determination in cm.
NUMBER	Number of integration steps.
MODE	Print out control for program monitoring = 0 for result print out only = 1 for minor progress report = 2 for print out of all calculations
III	Energy subscript for wave function print out.
MOMENTA	= 0 $\lambda = 0$ calculations only = 1 $\lambda = 1$ calculations only = 2 both $\lambda = 0$ and $\lambda = 1$ calculations.
FK	Wave number, k
FK2	Wave number squared, k^2 .
FMANY	MANY in floating point.
RA	Ratio of effective range to scattering length, r_0/a .
S	Well depth parameter, s

B	Intrinsic range, b
POT	Well depth, V_0
RN	Well range, r_n
ARGB	Bessel function argument, kr
VALUE	Output array of bessel functions
VALJ0	Spherical $l = 0$ bessel function, j
VALJ1	Spherical $l = 1$ bessel function, j_1
VALJ2	Spherical $l = 2$ bessel function, j_2
VALN0	Spherical $l = 0$ neumman function, n_0
VALN1	Spherical $l = 1$ neumann function, n_1
VALN2	Spherical $l = 2$ neumann function, n_2
A	A particular potential range from array, RN
V	A particular potential depth from array, POT
FNUMBER	Number of integration steps in floating point
STEP	integration step size
R	Array of radius values at each integration step
YVARS(1)	Wave function
YVARS(2)	Slope of wave functions
XVAR	Radius variable of integration
Y	Wave function at end value of integration step for $l = 0$.
YDOT	Slope of wave function at end value of integration step for $l = 0$.
COMPARO	Logarithmic derivative of wave function at end of integration range for $l = 0$.
COMPAR1	Logarithmic derivative of wave function at end of integration range for $l = 1$.
XC	Runge kutta weighted radius step

YC	Dependent variable for XC
DY	Derivative of dependent variable for XC
YL	Same as Y for $\lambda = 1$.
YLDOT	Same as YDOT for $\lambda = 1$.
DELTA0	$\lambda = 0$ phase shift.
DELTA1	$\lambda = 1$ phase shift.
XSEC0	$\lambda = 0$ cross section
XSEC1	$\lambda = 1$ cross section
TOTAL	Sum of singlet and triplet cross sections
BETTER	Normalized $\lambda = 0$ cross sections
FNORM	Base cross section to be used for normalization
NUMBERR	Number of simultaneous first order differential equations to be integrated.

APPENDIX III
PROGRAM LISTING


```

MAIN PROGRAM
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
2YDOT(1000), COMPARO(100), COMPARI(100), YL(1000),YLDOT(1000),POT(1
300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
40),FNORM(100),BETTER(10,100)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPARI,POT,VINT,VINC,MOMENTA,
3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
4TTER
  CALL INPUT2
  CALL READY2
  A=RN(MANY+1)
  V=POT(MANY+1)/.41499E-24
  CALL FIGURE
  CALL FINISH
  CALL APPEND
  DO 1 L=1,LL
  A=RN(L)
  V= POT(L)/.41499E-24
  CALL FIGURE
  CALL FINISH
  CALL OUTPUT2
  CALL SKETCH(E,XSECO,MOD,NUMPTS,II,L,LL)
1 CONTINUE
  CALL NOW(E,BETTER,II,L,LL)
  END

```



```

SUBROUTINE INPUT2
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
2YDOT(1000), COMPARO(100), COMPAR1(100), YL(1000),YLDOT(1000),POT(1
300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
40),FNORM(100),BETTER(10,100)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPAR1,POT,VINT,VINC,MOMENTA,
3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
4TTER
  READ 1,EINT,EINC,II
1 FORMAT(2E20.4,I10)
  READ 2,ROS,AS,CHANGE,MANY
2 FORMAT(2E20.6,F10.4,I10)
  READ 3,REND,NUMBER
3 FORMAT(E20.4,I10)
  READ 4,MODE
4 FORMAT(I10)
  READ 5,III
5 FORMAT(I10)
  READ 6,MOMENTA
6 FORMAT(I10)
  IF(MODE - 1) 8,8,7
7 PRINT 1,EINT,EINC,II
  PRINT 2,ROS,AS,CHANGE,MANY
  PRINT 3,REND,NUMBER
  PRINT 4,MODE
  PRINT 5,III
  PRINT 6,MOMENTA
8 RETURN
  END

```



```

SUBROUTINE FIGURE
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
2YDOT(1000), COMPARO(100), COMPAR1(100), YL(1000),YLDOT(1000),POT(1
300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
40),FNORM(100),BETTER(10,100)
  DIMENSION YVARS(30)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPAR1,POT,VINT,VINC,MOMENTA,
3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
4TTER
  FNUMBER = NUMBER
  STEP = REND / FNUMBER
  R(1) = 0.
  NN = NUMBER + 1
  DO 299 N=2,NN
299 R(N) = R(N-1) + STEP
  DO 292 K=2,II
  YVARS(1) = 0.
  YVARS(2) = 1.
  IF(MOMENTA - 1) 283,284,283
283 CALL RKUTTA(2,XVAR,YVARS,STEP)
  IF(K-III) 293,297,293
297 PRINT 296
296 FORMAT (13X,7H ENERGY,13X,7H RADIUS,6X,14H WAVE FUNCTION)
  PRINT 295,E(K)
295 FORMAT(F20.2)
  PRINT 294, (R(N), Y(N), N=1,NN)
294 FORMAT (E40.4,E20.4)
293 COMPARO(K)=YDOT(NN-1)/Y(NN-1)
284 IF (MOMENTA - 1) 292,291,291
291 YVARS(1) = 0.
  YVARS(2) = 1.
  CALL RKUTTA1(2,XVAR,YVARS,STEP)
  IF(K-III) 285,289,285
289 PRINT 288
288 FORMAT (13X,7H ENERGY,13X,7H RADIUS,6X,18H WAVE FUNCTION L=1)
  PRINT 287,E(K)
287 FORMAT(F20.2)
  PRINT 286, (R(N),YL(N),N=1,NN)
286 FORMAT(E40.4,E20.4)
285 COMPAR1(K)=YLDOT(NN-1)/YL(NN-1)
292 CONTINUE
  RETURN
  END

```



```

SUBROUTINE RKUTTA(NUMBERR,XVAR,YVARS,STEP)
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
1,VALJ2(100),VALN0(100),VALN1(100),VALN2(100),R(1000),Y(1000),
2YDOT(1000),COMPAR0(100),COMPAR1(100),YL(1000),YLDOT(1000),POT(1
300),DELTA0(100),DELTA1(100),XSEC0(100),XSEC1(100),TOTAL(100),RA(10
40),FNORM(100),BETTER(10,100)
  DIMENSION YVARS(30),AK(4,30),DY(30),YC(30),C(4)
  COMMON E,EINT,EINC,FK,FK2,RINT,RINC,RN,A,II,LL,NN,MODE,
1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M,NUMBER,R,I,L,V,K,
2N,Y,YDOT,YL,YLDOT,III,COMPAR0,COMPAR1,POT,VINT,VINC,MOMENTA,
3DELTA0,DELTA1,XSEC0,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
4TTER
  C(1)=0.0
  C(2)=0.5
  C(3)=0.5
  C(4)=1.0
  DO 298 N=1,NN
    XVAR = R(N)
    DO 1 I=1,4
      XC=XVAR + C(I)*STEP
      DO 2 J=1,NUMBERR
2 YC(J) =YVARS(J) + C(I)*AK(I-1,J)
      CALL DERIV(XC,YC,DY)
      DO 1 J=1,NUMBERR
1 AK(I,J) = STEP * DY(J)
      DO 3 J = 1,NUMBERR
3 YVARS(J) =YVARS(J) + (AK(1,J)+2.*AK(2,J)+2.*AK(3,J)+AK(4,J))/6.
      YDOT(N) = YVARS(2)
298 Y(N) = YVARS(1)
    RETURN
  END

```



```

SUBROUTINE RKUTTA1(NUMBERR,XVAR,YVARS,STEP)
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
2YDOT(1000), COMPARO(100), COMPARI(100), YL(1000),YLDOT(1000),POT(1
300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
40),FNORM(100),BETTER(10,100)
  DIMENSION YVARS(30),AK(4,30),DY(30),YC(30),C(4)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2, JJ,M, NUMBER, R,I,L,V,K,
2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPARI,POT,VINT,VINC,MOMENTA,
3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
4TTER
  C(1)=0.0
  C(2)=0.5
  C(3)=0.5
  C(4)=1.0
  DO 290 N=1,NN
    XVAR = R(N)
    DO 1 I=1,4
      XC=XVAR + C(I)*STEP
      DO 2 J=1,NUMBERR
        YC(J) =YVARS(J) + C(I)*AK(I-1,J)
        CALL DERIV1(XC,YC,DY)
        DO 1 J=1,NUMBERR
1      AK(I,J) = STEP * DY(J)
        DO 3 J = 1,NUMBERR
3      YVARS(J) =YVARS(J) + (AK(1,J)+2.*AK(2,J)+2.*AK(3,J)+AK(4,J))/6.
      YL(N) = YVARS(1)
290 YLDOT(N) = YVARS(2)
    RETURN
  END

```



```

SUBROUTINE FINISH
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPARI(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSEC0(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPARI,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSEC0,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  IF(MOMENTA - 1) 399,397,399
399 DO 398 I=2,II
  DELTA0(I)=ATANF((REND*(COMPARO(I)*VALJ0(I)+FK(I)*VALJ1(I))-
  1VALJ0(I))/(REND*(COMPARO(I)*VALN0(I)+FK(I)*VALN1(I))-
  2VALN0(I)))
398 XSEC0(I)=4.*3.1416/FK2(I)*SINF(DELTA0(I))*2
397 IF(MOMENTA-1)394,396,396
396 DO 395 I=2,II
  DELTA1(I)=ATANF((REND*(FK(I)/3.*VALJ0(I)-2./3.*FK(I)*
  1VALJ2(I)-COMPARI(I)*VALJ1(I))+VALJ1(I))/(REND*(FK(I)/3.*
  2VALN0(I)-2./3.*FK(I)*VALN2(I)-COMPARI(I)*VALN1(I))+VALN1(I)))
395 XSEC1(I)=12.*3.1416/FK2(I)*SINF(DELTA1(I))*2
390 DO 389 I = 2,II
389 TOTAL(I) = .25 * XSEC0(I) + .75 * XSEC1(I)
394 DO 900 I=2,II
  BETTER(L,I) = XSEC0(I)/FNORM(I)
900 CONTINUE
  RETURN
  END

```



```

SUBROUTINE OUTPUT2
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPAR1(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSEC0(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPAR1,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSEC0,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  PRINT 600,RA(L)
600  FORMAT(34H EFFECTIVE RANGE/SCATTERING LENGTH,/,E34.10)
  PRINT 599,A,POT(L)
599  FORMAT (13X,7H RADIUS,4X,16H POTENTIAL DEPTH,/,E20.4,E20.4)
  PRINT 598
598  FORMAT(7H ENERGY,12H PHASE ANGLE,15H CROSS SECTION,12H PHASE ANGLE
  1,15H CROSS SECTION,2X,6H TOTAL,/,11X,4H L=0,7X,4H L=0,10X,4H L=1,
  28X,4H L=1,8X,6H CROSS,/,63X,8H SECTION)
  PRINT 597,(E(I),DELTA0(I),XSEC0(I),DELTA1(I),XSEC1(I),TOTAL(I),I=2
  1,II)
597  FORMAT(F7.2,E12.4,E15.4,E12.4,E15.4,E11.4)
  PRINT 596
596  FORMAT(7H ENERGY,5X,25H NORMALIZED CROSS SECTION)
  PRINT 595,(E(I),BETTER(L,I),I=2,II)
595  FORMAT(F7.2,E20.8)
  RETURN
  END

```



```

SUBROUTINE BESSEL (X,N,VALUE,INDEX,MM)
DIMENSION VALUE(40),BJ(100),F(100)
IF (X) 10,10,9
9 IK=X/2.0
K=N+20+IK
IF(K-100) 300,299,299
299 PRINT 298
298 FORMAT(66H ARGUMENT PLUS ORDER TOO LARGE. INCREASE DIMENSIONS AND
1RUN AGAIN.)
RETURN
300 CONTINUE
Z=1.0/X
PI=3.141592653
GOTO(40,40,60,60,80,90,100,110),INDEX
10 PRINT 8,X
80FORMAT (1X,63H SUBROUTINE BESSEL DOES NOT WORK FOR X=0 OR LESS THAN
1: 0, HERE X= E15.8)
RETURN
40 BJ(K+1)=0.0
BJ(K)=10.0E-30
L=K
11 FL=L
BJ(L-1)=2.0*FL*Z*BJ(L)-BJ(L+1)
IF(L-1) 12,12,13
13 L=L-1
GO TO 11
12 SUM=0.0
IK=K
DO 14 I=2,IK,2
14 SUM=SUM+BJ(I)
C=1.0/(BJ(0)+2.0*SUM)
GO TO(42,43),INDEX
43 DO 45 I=0,K
45 BJ(I)=C*BJ(I)
GO TO 54
42 DO 41 I=0,N
41 VALUE(I)=C*BJ(I)
RETURN
50 GO TO 40
54 EC=.5772156649
SUM=0.0
IK=K/2
DO 15 I=1,IK
FI=I
15 SUM=SUM+((-1.0)**(I-1)*BJ(2*I))/FI
F(0)=(2.0/PI)*(BJ(0)*(LOGF(X/2.0)+EC)+2.0*SUM)
F(1)=(BJ(1)*F(0)-2.0/(PI*X))/BJ(0)
IN=N-1
DO 16 I=1,IN
FI=I

```



```

16 F(I+1)=2.0*FI*Z*F(I)-F(I-1)
   DO 51 I=0,N
51 VALUE(I)=F(I)
   RETURN
60 BJ(K+1)=0.
   BJ(K)=10.E-30
   L=K
19 FL=L
   BJ(L-1)=2.*FL*Z*BJ(L)+BJ(L+1)
   IF(L-1)17,17,18
18 L=L-1
   GO TO 19
17 SUM=0.0
   DO 21 I=1,K
21 SUM=SUM+BJ(I)
   C=(EXPF(X))/(BJ(0)+2.*SUM)
   GO TO(1,1,61,62),INDEX
1 PRINT 1000
   RETURN
1000 FORMAT(40H CARD MISSING. IGNORE RESULTS.
62 DO 64 I=0,1
64 BJ(I)=C*BJ(I)
   GO TO 71
61 DO 65 I=0,N
65 VALUE(I)=C*BJ(I)
   RETURN
70 GO TO 60
71 IF(5.0-X) 120,121,121
121 M=10
   GO TO 122
120 M=5
122 F(0)=GAUSS(0.0,1.0,M,X)
   F(1)=(1./X-F(0)*BJ(1))/BJ(0)
   IN=N-1
   DO 22 I=1,IN
   FI=I
22 F(I+1)=2.0*FI*Z*F(I)+F(I-1)
   DO 72 I=0,N
72 VALUE(I)=F(I)
   RETURN
80 F(K+1)=0.0
   F(K)=10.0E-30
   L=K
25 FL=L
   F(L-1)=(2.0*FL+1.0)*Z*F(L)-F(L+1)
   IF(L-1) 23,23,24
24 L=L-1
   GO TO 25
23 C=SINF(X)/(X*F(0))
   IF(MM)200,200,201
201 SQ=SQRTF(2.*X/PI)
   DO 202 I=0,N
202 VALUE(I)=C*SQ*F(I)
   RETURN

```



```

200 DO 26 I=0,N
26 VALUE(I)=C*F (I)
RETURN
90 F (0)=-COSF(X)/X
F (1)=-SINF(X)/X-COSF(X)/X**2
IN=N-1
DO 27 I=1,IN
FI=I
27 F(I+1)=(2.*FI+1.0)*Z*F(I)-F(I-1)
IF(MM) 203,203,204
204 SQ=SQRTF(2.*X/PI)
DO 205 I=0,N
205 VALUE(I)=F (I)*SQ*(-1.)**(-I-1)
RETURN
203 DO 91 I=0,N
91 VALUE(I)=F (I)
RETURN
100 F (K+1)=0.0
F (K)=10.0E-30
L=K
30 FL=L
F (L-1)=(2.0*FL+1.0)*Z*F (L)+F (L+1)
IF (L-1) 28,28,29
29 L=L-1
GO TO 30
28 C=SINH (X)/(X*F (0))
IF(MM) 206,206,207
207 SQ=SQRTF(2.*X/PI)
DO 208 I=0,N
208 VALUE(I)=C*SQ*F (I)
RETURN
206 DO 101 I=0,N
101 VALUE(I)=C*F (I)
RETURN
110 F (0)=-PI*EXPF(-X)/(2.0*X)
F (1)=(PI*(X+1.0)*EXPF(-X))/(2.0*X**2)
IN=N-1
DO 31 I=1,IN
FI=I
31 F (I+1)=F (I-1)-(2.0*FI+1.0)*Z*F (I)
IF(MM) 209,209,210
210 SQ=SQRTF(2.*X/PI)
DO 211 I=0,N
211 VALUE(I)=F (I)*SQ*(-1.)**(-I-1)
RETURN
209 DO 111 I=0,N
111 VALUE(I)=F (I)
RETURN
END

```

C FUNCTION GAUSS NUMERICAL INTERGRATION

C FUNCTION GAUSS REQUIRES FUNCTION GAUSSF(X) NUMERICAL INTERGRATION

FUNCTION GAUSS(G,B,M,X)

DIMENSION R(10),U(10)

U(1)=+.0744371695


```

U(2)=-.0744371695
U(3)=+.2166976971
U(4)=-.2166976971
U(5)=+.3397047841
U(6)=-.3397047841
U(7)=+.4325316833
U(8)=-.4325316833
U(9)=+.4869532643
U(10)=-.4869532643
R(1)=+.1477621124
R(2)=+.1477621124
R(3)=+.1346333597
R(4)=+.1346333597
R(5)=.10954318113
R(6)=.10954318113
R(7)=+.07472567458
R(8)=+.07472567458
R(9)=+.03333567215
R(10)=+.03333567215
A=G
FN=M
P=(B-A)/FN
GAUSS=0.0
DO 1 J=1,M
C=0.0
Y=A+P
DO 2 I=1,10
D=(R(I)*GAUSSF((Y-A)*U(I)+(A+Y)/2.0,X))*(Y-A)
2 C=D+C
A=Y
1 GAUSS=GAUSS +C
RETURN
END
FUNCTION GAUSSF(U,X)
IF(1.0/U-710.0)123,124,124
124 GAUSSF=0.0
RETURN
123 GAUSSF= (EXP(-X*COSH(1.0/U-1.0)))/U**2
END

```



```

SUBROUTINE SKETCH(E,XSECO,MOD,NUMPTS,II,L,LL)
DIMENSION E(100),XSECO(100),XSEC1(100),TOTAL(100)
DIMENSION X(900),Y(900),ITITLE(12)
LABEL = 4H
DO 1 I=1,12
1 ITITLE(I) = 8H
  ITITLE(1)=8HOSGOOD,F
  ITITLE(2)=8H.B.,BOX
  ITITLE(3)=8H09
  ITITLE(4)=8HEXPONENT
  ITITLE(5)=8HIAL WELL
  ITITLE(6)=8H RUN 15
  ITITLE(7)=8H GRAPH O
  ITITLE(8)=8HF CROSS
  ITITLE(9)=8HSECTION
  ITITLE(10)=8HVS ENERG
  ITITLE(11)=8HY FOR L=
  ITITLE(12) = 8H0
NUMPTS = II-1
IF(L-1)2,2,3
2 MOD = 1
  GO TO 6
3 IF(LL-L) 5,5,4
4 MOD = 2
  GO TO 6
5 MOD = 3
6 CONTINUE
  CALL DRAW(NUMPTS,E,XSECO,MOD,0,LABEL,ITITLE,.3,0,0,0,0,0,9,15,1,L
1AST)
  RETURN
END

```



```

SUBROUTINE APPEND
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPAR1(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSEC0(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPAR1,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSEC0,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  DO 1 I=2,II
1  FNORM(I) = XSEC0(I)
  RETURN
END

```



```

SUBROUTINE NOW(E,BETTER,II,L,LL)
DIMENSION E(100), BETTER(10,100),X(900),Y(900),ITITLE(12)
LABEL = 4H
DO 1 I=1,12
1 ITITLE(I)=8H
ITITLE(1)=8HOSGOOD,F
ITITLE(2)=8H.B.,BOX
ITITLE(3)=8H09
ITITLE(7)=8HNORMALIZ
ITITLE(8)=8HED CROSS
ITITLE(9)=8H SECTION
ITITLE(10)=8H FOR L=0
NUMPTS = II-1
DO 7 L=1,LL
IF(L-1) 2,2,3
2 MOD=1
GO TO 6
3 IF(LL-L) 5,5,4
4 MOD = 2
GO TO 6
5 MOD = 3
6 CONTINUE
DO 20 I=2,II
20 BET(I)=BETTER(L,I)
CALL DRAW(NUMPTS,E,BET, MOD,0,LABEL,ITITLE,.3,0,0,0,0,0,9,15,1,L
1AST)
7 CONTINUE
RETURN
END

```


THE FOLLOWING SUBROUTINES ARE DEPENDENT UPON A PARTICULAR POTENTIAL SHAPE.

GAUSSIAN POTENTIAL

```

SUBROUTINE READY2
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPARI(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSEC0(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  DIMENSION VALUE(40)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPARI,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSEC0,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  E(1) = EINT
  DO 199 I = 2,II
    E(I) = E(I-1) + EINC
    FK(I) = SQRTF(E(I)/.41499E-24)
199 FK2(I)= FK(I) * FK(I)
    LL=2*MANY + 1
    JJ=LL
    FMANY = MANY
    GAUSSIAN DISTRIBUTION
    RA(1) = ROS/AS*(1.- FMANY*CHANGE)
    DO 170 L=1,LL
      S=(1.-2.03*RA(L)+.587*RA(L)**2)/(1.-2.81*RA(L)+1.805*RA(L)**2)
      SS=S-1.
      B=RA(L)*AS/(1.-.641*SS+.568*SS**2-.721*SS**3+1.172*SS**4-1.015*SS*
1*5)
      POT(L)=S*.229208E-23/B**2
      RN(L)=SQRTF(B**2/2.0604)
170 RA(L+1) = RA(L) + CHANGE *ROS/AS
      IF(MODE - 1) 190,192,197
197 PRINT 196
196 FORMAT (13X,7H ENERGY,5X,12H WAVE NUMBER,3X,20H WAVE NUMBER SQUARE
1D)
      PRINT 195 ,(E(I), FK(I),FK2(I),I=2,II)
195 FORMAT (3E20.4)
      PRINT 171
171 FORMAT(34H EFFECTIVE RANGE/SCATTERING LENGTH)
      PRINT 172,(RA(L) L=1,LL)
172 FORMAT(E34.10)
      PRINT 194
194 FORMAT (13X,7H RADIUS)
      PRINT 193, (RN(L), L=1,LL)
193 FORMAT (E20.4)
      PRINT 1192
1192 FORMAT (16H POTENTIAL DEPTH)
      PRINT 2192,(POT(J),J=1,JJ)
2192 FORMAT(F16.2)
192 PRINT 191

```



```

191 FORMAT( 34H RADIUS AND ENERGY VALUES COMPUTED)
190 DO 187 I=2,II
    ARGB      = FK(I) * REND
    CALL BESSEL( ARGB,2,VALUE,5, 0)
    VALJ0(I) = VALUE(0)
    VALJ1(I) = VALUE(1)
    VALJ2(I) = VALUE(2)
    CALL BESSEL (ARGB,2,VALUE, 6,0)
    VALN0(I) = VALUE(0)
    VALN1(I) = VALUE(1)
    VALN2(I) = VALUE(2)
    IF(MODE - 1) 187,187,189
189 PRINT 188,I
188 FORMAT(14I5)
187 CONTINUE
    IF(MODE - 1) 184,186,186
186 PRINT 185
185 FORMAT( 26H BESSEL FUNCTIONS COMPUTED)
184 RETURN
    END

```


EXPONENTIAL POTENTIAL

```

SUBROUTINE READY2
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPARI(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  DIMENSION VALUE(40)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2, JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPARI,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  E(1) = EINT
  DO 199 I = 2,II
    E(I) = E(I-1) + EINC
    FK(I) = SQRTF(E(I)/.41499E-24)
199 FK2(I)= FK(I) * FK(I)
  LL=2*MANY + 1
  JJ=LL
  EXPONENTIAL WELL
  FMANY = MANY
  RA(1)=ROS/AS*(1.+FMANY*CHANGE)
  DO 170 L=1,LL
    S=(1.-2.9739*RA(L)+1.3602*RA(L)**2)/(1.-3.7134*RA(L)+3.1177*RA(L)*
    1*2)
    SS=S-1.
    B=RA(L)*AS/(1.-.904*SS+.745*SS**2-.542*SS**3+.174*SS**4)
    POT(L)=S*.751541E-23/B**2
    RN(L)=B/3.5412
170 RA(L+1) = RA(L) - CHANGE *ROS/AS
    IF(MODE - 1) 190,192,197
197 PRINT 196
196 FORMAT (13X,7H ENERGY,5X,12H WAVE NUMBER,3X,20H WAVE NUMBER SQUARE
  1D)
  PRINT 195 ,(E(I), FK(I),FK2(I),I=2,II)
195 FORMAT (3E20.4)
  PRINT 171
171 FORMAT(34H EFFECTIVE RANGE/SCATTERING LENGTH)
  PRINT 172,(RA(L) L=1,LL)
172 FORMAT(E34.10)
  PRINT 194
194 FORMAT (13X,7H RADIUS)
  PRINT 193, (RN(L), L=1,LL)
193 FORMAT (E20.4)
  PRINT 1192
192 FORMAT (16H POTENTIAL DEPTH)
  PRINT 2192,(POT(J),J=1,JJ)
192 FORMAT(F16.2)
192 PRINT 191

```



```

191 FORMAT( 34H RADIUS AND ENERGY VALUES COMPUTED)
190 DO 187 I=2,II
    ARGB      = FK(I) * REND
    CALL BESSEL( ARGB,2,VALUE,5, 0)
    VALJ0(I) = VALUE(0)
    VALJ1(I) = VALUE(1)
    VALJ2(I) = VALUE(2)
    CALL BESSEL (ARGB,2,VALUE, 6,0)
    VALN0(I) = VALUE(0)
    VALN1(I) = VALUE(1)
    VALN2(I) = VALUE(2)
    IF(MODE - 1) 187,187,189
189 PRINT 188,I
188 FORMAT(14I5)
187 CONTINUE
    IF(MODE - 1) 184,186,186
186 PRINT 185
185 FORMAT( 26H BESSEL FUNCTIONS COMPUTED)
184 RETURN
    END

```


YUKAWA POTENTIAL

SUBROUTINE READY2

```
DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
2YDOT(1000), COMPARO(100), COMPAR1(100), YL(1000),YLDOT(1000),POT(1
300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
40),FNORM(100),BETTER(10,100)
```

```
DIMENSION VALUE(40)
```

```
COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPAR1,POT,VINT,VINC,MOMENTA,
3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
4TTER
```

```
E(1) = EINT
```

```
DO 199 I = 2,II
```

```
E(I) = E(I-1) + EINC
```

```
FK(I) = SQRTF(E(I)/.41499E-24)
```

```
199 FK2(I)= FK(I) * FK(I)
```

```
LL=2*MANY + 1
```

```
JJ=LL
```

```
FMANY = MANY
```

```
RA(1)=ROS/AS*(1.+FMANY*CHANGE)
```

```
YUKAWA WELL
```

```
DO 170 L=1,LL
```

```
S=(1.-3.5093*RA(L)+2.0354*RA(L)**2)/(1.-4.1348*RA(L)+3.7072*RA(L)*
1*2)
```

```
SS=S-1.
```

```
B=RA(L)*AS/(1.-1.369*SS+1.093*SS**2-1.127*SS**3+1.005*SS**4-.324*S
1S**5)
```

```
POT(L)=S*.147585E-23*2.1196/B**2
```

```
RN(L)=B/2.1196
```

```
170 RA(L+1) = RA(L) - CHANGE *ROS/AS
```

```
IF(MODE - 1) 190,192,197
```

```
197 PRINT 196
```

```
196 FORMAT (13X,7H ENERGY,5X,12H WAVE NUMBER,3X,20H WAVE NUMBER SQUARE
1D)
```

```
PRINT 195 ,(E(I), FK(I),FK2(I),I=2,II)
```

```
195 FORMAT (3E20.4)
```

```
PRINT 171
```

```
171 FORMAT(34H EFFECTIVE RANGE/SCATTERING LENGTH)
```

```
PRINT 172,(RA(L) L=1,LL)
```

```
172 FORMAT(E34.10)
```

```
PRINT 194
```

```
194 FORMAT (13X,7H RADIUS)
```

```
PRINT 193, (RN(L), L=1,LL)
```

```
193 FORMAT (E20.4)
```

```
PRINT 1192
```

```
1192 FORMAT (16H POTENTIAL DEPTH)
```

```
PRINT 2192,(POT(J),J=1,JJ)
```

```
2192 FORMAT(F16.2)
```



```

192 PRINT 191
191 FORMAT( 34H RADIUS AND ENERGY VALUES COMPUTED)
190 DO 187 I=2,II
    ARGB      = FK(I) * REND
    CALL BESSEL( ARGB,2,VALUE,5, 0)
    VALJ0(I) = VALUE(0)
    VALJ1(I) = VALUE(1)
    VALJ2(I) = VALUE(2)
    CALL BESSEL (ARGB,2,VALUE, 6,0)
    VALN0(I) = VALUE(0)
    VALN1(I) = VALUE(1)
    VALN2(I) = VALUE(2)
    IF(MODE - 1) 187,187,189
189 PRINT 188,I
188 FORMAT(14I5)
187 CONTINUE
    IF(MODE - 1) 184,186,186
186 PRINT 185
185 FORMAT( 26H BESSEL FUNCTIONS COMPUTED)
184 RETURN
    END

```


SQUARE WELL POTENTIAL

```

SUBROUTINE READY2
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPARI(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  DIMENSION VALUE(40)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPARI,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  E(1) = EINT
  DO 199 I = 2,II
    E(I) = E(I-1) + EINC
    FK(I) = SQRTF(E(I)/.41499E-24)
199  FK2(I)= FK(I) * FK(I)
    LL=2*MANY + 1
    JJ=LL
    SQUARE WELL
    FMANY = MANY
    CHANGE SIGN TO - FOR NORMAL OPERATION
    RA(1)=ROS/AS*(1.+FMANY*CHANGE)
    DO 170 L=1,LL
      S=(1.-1.574*RA(L)+.353*RA(L)**2)/(1.-2.384*RA(L)+1.30*RA(L)**2)
      SS=S-1.
      B=RA(L)*AS/(1.-.5*SS+.486*SS**2-.476*SS**3+.378*SS**4-.158*SS**5)
      POT(L) = S*.102276E-23/B**2
      RN(L) =B
170  RA(L+1) = RA(L) - CHANGE *ROS/AS
      IF(MODE - 1) 190,192,197
197  PRINT 196
196  FORMAT (13X,7H ENERGY,5X,12H WAVE NUMBER,3X,20H WAVE NUMBER SQUARE
10)
      PRINT 195 ,(E(I), FK(I),FK2(I),I=2,II)
195  FORMAT (3E20.4)
      PRINT 171
171  FORMAT(34H EFFECTIVE RANGE/SCATTERING LENGTH)
      PRINT 172,(RA(L) L=1,LL)
172  FORMAT(E34.10)
      PRINT 194
194  FORMAT (13X,7H RADIUS)
      PRINT 193, (RN(L), L=1,LL)
193  FORMAT (E20.4)
      PRINT 1192
1192  FORMAT (16H POTENTIAL DEPTH)
      PRINT 2192,(POT(J),J=1,JJ)
2192  FORMAT(F16.2)
192  PRINT 191

```



```

191 FORMAT( 34H RADIUS AND ENERGY VALUES COMPUTED)
190 DO 187 I=2,II
    ARGB      = FK(I) * REND
    CALL BESSEL( ARGB,2,VALUE,5, 0)
    VALJ0(I) = VALUE(0)
    VALJ1(I) = VALUE(1)
    VALJ2(I) = VALUE(2)
    CALL BESSEL (ARGB,2,VALUE, 6,0)
    VALN0(I) = VALUE(0)
    VALN1(I) = VALUE(1)
    VALN2(I) = VALUE(2)
    IF(MODE - 1) 187,187,189
189 PRINT 188,I
188 FORMAT(14I5)
187 CONTINUE
    IF(MODE - 1) 184,186,186
186 PRINT 185
185 FORMAT( 26H BESSEL FUNCTIONS COMPUTED)
184 RETURN
    END

```


GAUSSIAN POTENTIAL

```

SUBROUTINE DERIV (XC,YC,DY)
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPAR1(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  DIMENSION YC(30), DY(30)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPAR1,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  DY(1) =YC(2)
  DY(2) = - (FK2(K) + V * EXPF(-(XC/A) ** 2)) * YC(1)
  RETURN
  END

```

```

SUBROUTINE DERIV1(XC,YC,DY)
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPAR1(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  DIMENSION YC(30), DY(30)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPAR1,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  DY(1) = YC(2)
  DY(2) = -(FK2(K) + V * EXPF(-(XC/A)**2) - 2./XC**2)*YC(1)
  RETURN
  END

```


EXPONENTIAL POTENTIAL

```

SUBROUTINE DERIV (XC,YC,DY)
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPAR1(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  DIMENSION YC(30), DY(30)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPAR1,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  DY(1) = YC(2)
  DY(2) = - (FK2(K) + V * EXPF(-      XC/A)) * YC(1)
  RETURN
END

```

```

SUBROUTINE DERIV1(XC,YC,DY)
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPAR1(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  DIMENSION YC(30), DY(30)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPAR1,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  DY(1) = YC(2)
  DY(2) = - (FK2(K) + V * EXPF(-      XC/A) -2. /XC**2)*YC(1)
  RETURN
END

```


YUKAWA POTENTIAL

```

SUBROUTINE DERIV (XC,YC,DY)
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
2YDOT(1000), COMPARO(100), COMPARI(100), YL(1000),YLDOT(1000),POT(1
300),DELTA0(100),DELTA1(100),XSEC0(100),XSEC1(100),TOTAL(100),RA(10
40),FNORM(100),BETTER(10,100)
  DIMENSION YC(30), DY(30)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPARI,POT,VINT,VINC,MOMENTA,
3DELTA0,DELTA1,XSEC0,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
4TTER
  DY(1) = YC(2)
  DY(2) = - (FK2(K) + V * (EXPF(-XC/A))/(XC/A))*YC(1)
  RETURN
  END

```

```

SUBROUTINE DERIV1(XC,YC,DY)
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
2YDOT(1000), COMPARO(100), COMPARI(100), YL(1000),YLDOT(1000),POT(1
300),DELTA0(100),DELTA1(100),XSEC0(100),XSEC1(100),TOTAL(100),RA(10
40),FNORM(100),BETTER(10,100)
  DIMENSION YC(30), DY(30)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPARI,POT,VINT,VINC,MOMENTA,
3DELTA0,DELTA1,XSEC0,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
4TTER
  DY(1) = YC(2)
  DY(2) = - (FK2(K) + V * (EXPF(-XC/A))/(XC/A) -2./XC**2) * YC(1)
  RETURN
  END

```


SQUARE WELL POTENTIAL

```

SUBROUTINE DERIV (XC,YC,DY)
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPARI(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  DIMENSION YC(30), DY(30)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPARI,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  DY(1) =YC(2)
  IF(XC -A) 1,1,2
1 DY(2) = -(FK2(K) + V) * YC(1)
  RETURN
2 DY(2) =-(FK2(K))* YC(1)
  RETURN
  END

```

```

SUBROUTINE DERIV1(XC,YC,DY)
  DIMENSION E(100),FK(100),FK2(100),RN(100),VALJ0(100),VALJ1(100)
  1,VALJ2(100), VALN0(100), VALN1(100),VALN2(100), R(1000), Y(1000),
  2YDOT(1000), COMPARO(100), COMPARI(100), YL(1000),YLDOT(1000),POT(1
  300),DELTA0(100),DELTA1(100),XSECO(100),XSEC1(100),TOTAL(100),RA(10
  40),FNORM(100),BETTER(10,100)
  DIMENSION YC(30), DY(30)
  COMMON E,EINT,EINC, FK, FK2, RINT, RINC, RN, A, II, LL, NN, MODE,
  1REND,VALJ0,VALJ1,VALJ2,VALN0,VALN1,VALN2,JJ,M, NUMBER, R,I,L,V,K,
  2N,Y, YDOT, YL, YLDOT, III, COMPARO, COMPARI,POT,VINT,VINC,MOMENTA,
  3DELTA0,DELTA1,XSECO,XSEC1,TOTAL,RA,ROS,AS,CHANGE,MANY,S,B,FNORM,BE
  4TTER
  DY(1) =YC(2)
  IF(XC -A) 1,1,2
1 DY(2) = -(FK2(K) + V - 2./XC**2)*YC(1)
  RETURN
2 DY(2) = -(FK2(K) - 2./ XC**2) *YC(1)
  RETURN
  END

```


THE FOLLOWING DEFINITIONS FOR B MUST BE SUBSTITUTED IN READY2 FOR VARYING
SCATTERING LENGTH. THE DEFINITION PROVIDED IN READY2 IN THE LISTING IS FOR
VARIATIONS IN EFFECTIVE RANGE.

YUKAWA WELL

$$B = ROS / (1. - 1.369 * SS + 1.093 * SS ** 2 - 1.127 * SS ** 3 + 1.005 * SS ** 4 - .324 * SS ** 5)$$

SQUARE WELL

$$B = ROS / (1. - .5 * (S - 1.) + .486 * (S - 1.) ** 2 - .476 * (S - 1.) ** 3 + .378 * (S - 1.) ** 4 \\ - .158 * (S - 1.) ** 5)$$

EXPONENTIAL WELL

$$B = ROS / (1. - .904 * SS + .745 * SS ** 2 - .543 * SS ** 3 + .174 * SS ** 4)$$

GAUSSIAN WELL

$$B = ROS / (1. - .641 * SS + .568 * SS ** 2 - .721 * SS ** 3 + 1.172 * SS ** 4 - 1.015 * SS ** 5)$$

APPENDIX IV

SAMPLE RESULTS

These results are for a yukawa potential with $r_{o,s}^*$ fixed at 2.46 Fm and a_s varying in $\pm 16\%$ deviation from $a_s^* = 23.677$ FM.

EFFECTIVE RANGE/SCATTERING LENGTH
 - .8727457026E-01
 RADIUS POTENTIAL DEPTH
 .1086E-12 .5621E+02
 ENERGY PHASE ANGLE CROSS SECTION,
 L=0 L=0

.10	.9113E+00	.3257E-22
.20	.1037E+01	.1933E-22
.30	.1094E+01	.1372E-22
.40	.1125E+01	.1062E-22
.50	.1145E+01	.8649E-23
.60	.1158E+01	.7290E-23
.70	.1166E+01	.6295E-23
.80	.1172E+01	.5535E-23
.90	.1176E+01	.4936E-23
1.00	.1178E+01	.4451E-23
1.10	.1180E+01	.4051E-23
1.20	.1180E+01	.3716E-23
1.30	.1180E+01	.3430E-23
1.40	.1180E+01	.3184E-23
1.50	.1179E+01	.2970E-23
1.60	.1178E+01	.2781E-23
1.70	.1176E+01	.2615E-23
1.80	.1175E+01	.2466E-23
1.90	.1173E+01	.2333E-23
2.00	.1172E+01	.2213E-23
2.10	.1170E+01	.2105E-23
2.20	.1168E+01	.2006E-23
2.30	.1166E+01	.1915E-23
2.40	.1164E+01	.1832E-23
2.50	.1161E+01	.1755E-23
2.60	.1159E+01	.1685E-23
ENERGY	NORMALIZED CROSS SECTION	
.10	.11366967E+C1	
.20	.10869311E+C1	
.30	.10658047E+C1	
.40	.10541020E+01	
.50	.10466564E+01	
.60	.10414947E+01	
.70	.10377002E+01	
.80	.10347892E+01	
.90	.10324821E+01	
1.00	.10306062E+01	
1.10	.10290489E+01	
1.20	.10277338E+01	
1.30	.10266071E+01	
1.40	.10256300E+01	
1.50	.10247736E+01	
1.60	.10240161E+01	
1.70	.10233405E+01	
1.80	.10227338E+01	
1.90	.10221853E+01	
2.00	.10216868E+01	
2.10	.10212311E+01	
2.20	.10208129E+01	
2.30	.10204272E+01	
2.40	.10200702E+01	
2.50	.10197386E+01	
2.60	.10194296E+01	

EFFECTIVE RANGE/SCATTERING LENGTH
 - .9143050217E-01
 RADIUS POTENTIAL DEPTH
 .1083E-12 .5641E+02
 ENERGY PHASE ANGLE CROSS SECTION,
 L=0 L=0

.10	.8913E+00	.3155E-22
.20	.1020E+01	.1894E-22
.30	.1079E+01	.1351E-22
.40	.1112E+01	.1048E-22
.50	.1133E+01	.8553E-23
.60	.1146E+01	.7218E-23
.70	.1156E+01	.6238E-23
.80	.1162E+01	.5489E-23
.90	.1166E+01	.4897E-23
1.00	.1169E+01	.4419E-23
1.10	.1171E+01	.4023E-23
1.20	.1172E+01	.3691E-23
1.30	.1172E+01	.3408E-23
1.40	.1172E+01	.3164E-23
1.50	.1172E+01	.2952E-23
1.60	.1171E+01	.2765E-23
1.70	.1170E+01	.2600E-23
1.80	.1168E+01	.2453E-23
1.90	.1167E+01	.2321E-23
2.00	.1165E+01	.2202E-23
2.10	.1164E+01	.2094E-23
2.20	.1162E+01	.1995E-23
2.30	.1160E+01	.1906E-23
2.40	.1158E+01	.1823E-23
2.50	.1156E+01	.1747E-23
2.60	.1154E+01	.1677E-23

ENERGY	NORMALIZED CROSS SECTION
.10	.110114334E+01
.20	.10649739E+01
.30	.10493686E+01
.40	.10406591E+01
.50	.10350936E+01
.60	.10312243E+01
.70	.10283743E+01
.80	.10261847E+01
.90	.10244473E+01
1.00	.10230335E+01
1.10	.10218590E+01
1.20	.10208666E+01
1.30	.10200161E+01
1.40	.10192782E+01
1.50	.10186313E+01
1.60	.10180589E+01
1.70	.10175484E+01
1.80	.10170898E+01
1.90	.10166753E+01
2.00	.10162984E+01
2.10	.10159539E+01
2.20	.10156377E+01
2.30	.10153461E+01
2.40	.10150762E+01
2.50	.10148255E+01
2.60	.10145919E+01

EFFECTIVE RANGE/SCATTERING LENGTH

- .9558643409E-01

RADIUS

POTENTIAL DEPTH

.1080E-12

.5661E+02

ENERGY PHASE ANGLE CROSS SECTION,

L=0

L=0

.10	.8719E+00	.3056E-22
.20	.1004E+01	.1855E-22
.30	.1064E+01	.1329E-22
.40	.1099E+01	.1034E-22
.50	.1121E+01	.8457E-23
.60	.1135E+01	.7145E-23
.70	.1145E+01	.6181E-23
.80	.1152E+01	.5443E-23
.90	.1157E+01	.4859E-23
1.00	.1161E+01	.4386E-23
1.10	.1163E+01	.3994E-23
1.20	.1164E+01	.3666E-23
1.30	.1165E+01	.3386E-23
1.40	.1165E+01	.3144E-23
1.50	.1165E+01	.2934E-23
1.60	.1164E+01	.2749E-23
1.70	.1163E+01	.2585E-23
1.80	.1162E+01	.2439E-23
1.90	.1161E+01	.2308E-23
2.00	.1159E+01	.2190E-23
2.10	.1158E+01	.2083E-23
2.20	.1156E+01	.1985E-23
2.30	.1154E+01	.1896E-23
2.40	.1152E+01	.1814E-23
2.50	.1150E+01	.1738E-23
2.60	.1148E+01	.1669E-23

ENERGY

NORMALIZED CROSS SECTION

.10	.10664810E+01
.20	.10431380E+01
.30	.10329030E+01
.40	.10271472E+01
.50	.10234527E+01
.60	.10208768E+01
.70	.10189756E+01
.80	.10175126E+01
.90	.10163506E+01
1.00	.10154041E+01
1.10	.10146173E+01
1.20	.10139521E+01
1.30	.10133817E+01
1.40	.10128867E+01
1.50	.10124526E+01
1.60	.10120684E+01
1.70	.10117257E+01
1.80	.10114178E+01
1.90	.10111394E+01
2.00	.10108863E+01
2.10	.10106549E+01
2.20	.10104425E+01
2.30	.10102467E+01
2.40	.10100654E+01
2.50	.10098970E+01
2.60	.10097400E+01

EFFECTIVE RANGE/SCATTERING LENGTH
 - .9974236601E-01
 RADIUS POTENTIAL DEPTH
 .1077E-12 .5680E+02
 ENERGY PHASE ANGLE CROSS SECTION,
 L=0 L=0

.10	.8531E+00	.2959E-22
.20	.9875E+00	.1817E-22
.30	.1050E+01	.1308E-22
.40	.1086E+01	.1021E-22
.50	.1109E+01	.8360E-23
.60	.1125E+01	.7073E-23
.70	.1135E+01	.6124E-23
.80	.1143E+01	.5396E-23
.90	.1148E+01	.4820E-23
1.00	.1152E+01	.4352E-23
1.10	.1155E+01	.3966E-23
1.20	.1156E+01	.3641E-23
1.30	.1157E+01	.3363E-23
1.40	.1158E+01	.3124E-23
1.50	.1157E+01	.2916E-23
1.60	.1157E+01	.2733E-23
1.70	.1156E+01	.2570E-23
1.80	.1155E+01	.2425E-23
1.90	.1154E+01	.2296E-23
2.00	.1153E+01	.2178E-23
2.10	.1152E+01	.2072E-23
2.20	.1150E+01	.1975E-23
2.30	.1148E+01	.1886E-23
2.40	.1147E+01	.1805E-23
2.50	.1145E+01	.1730E-23
2.60	.1143E+01	.1661E-23

ENERGY	NORMALIZED CROSS SECTION
.10	.10327555E+01
.20	.10214671E+01
.30	.10164376E+01
.40	.10135874E+01
.50	.10117498E+01
.60	.10104647E+01
.70	.10095142E+01
.80	.10087817E+01
.90	.10081992E+01
1.00	.10077243E+01
1.10	.10073292E+01
1.20	.10069950E+01
1.30	.10067083E+01
1.40	.10064594E+01
1.50	.10062411E+01
1.60	.10060478E+01
1.70	.10058753E+01
1.80	.10057203E+01
1.90	.10055802E+01
2.00	.10054527E+01
2.10	.10053363E+01
2.20	.10052293E+01
2.30	.10051307E+01
2.40	.10050394E+01
2.50	.10049546E+01
2.60	.10048756E+01

EFFECTIVE RANGE/SCATTERING LENGTH

- .1038982979E+00

RADIUS

POTENTIAL DEPTH

.1074E-12

.5700E+02

ENERGY PHASE ANGLE CROSS SECTION,

L=0

L=0

.10	.8350E+00	.2866E-22
.20	.9717E+00	.1778E-22
.30	.1036E+01	.1287E-22
.40	.1074E+01	.1007E-22
.50	.1098E+01	.8263E-23
.60	.1114E+01	.6999E-23
.70	.1125E+01	.6066E-23
.80	.1133E+01	.5349E-23
.90	.1139E+01	.4781E-23
1.00	.1143E+01	.4319E-23
1.10	.1146E+01	.3937E-23
1.20	.1148E+01	.3615E-23
1.30	.1150E+01	.3341E-23
1.40	.1150E+01	.3104E-23
1.50	.1150E+01	.2898E-23
1.60	.1150E+01	.2716E-23
1.70	.1150E+01	.2555E-23
1.80	.1149E+01	.2412E-23
1.90	.1148E+01	.2283E-23
2.00	.1147E+01	.2166E-23
2.10	.1146E+01	.2061E-23
2.20	.1144E+01	.1965E-23
2.30	.1143E+01	.1877E-23
2.40	.1141E+01	.1796E-23
2.50	.1140E+01	.1721E-23
2.60	.1138E+01	.1653E-23

ENERGY NORMALIZED CROSS SECTION

.10	.10000000E+01
.20	.10000000E+01
.30	.10000000E+01
.40	.10000000E+01
.50	.10000000E+01
.60	.10000000E+01
.70	.10000000E+01
.80	.10000000E+01
.90	.10000000E+01
1.00	.10000000E+01
1.10	.10000000E+01
1.20	.10000000E+01
1.30	.10000000E+01
1.40	.10000000E+01
1.50	.10000000E+01
1.60	.10000000E+01
1.70	.10000000E+01
1.80	.10000000E+01
1.90	.10000000E+01
2.00	.10000000E+01
2.10	.10000000E+01
2.20	.10000000E+01
2.30	.10000000E+01
2.40	.10000000E+01
2.50	.10000000E+01
2.60	.10000000E+01

EFFECTIVE RANGE/SCATTERING LENGTH
 - .1080542298E+00
 RADIUS POTENTIAL DEPTH
 .1071E-12 .5719E+02
 ENERGY PHASE ANGLE CROSS SECTION,
 L=0 L=0

.10	.8175E+00	.2775E-22
.20	.9562E+00	.1741E-22
.30	.1022E+01	.1266E-22
.40	.1061E+01	.9934E-23
.50	.1086E+01	.8166E-23
.60	.1103E+01	.6926E-23
.70	.1115E+01	.6008E-23
.80	.1124E+01	.5302E-23
.90	.1130E+01	.4741E-23
1.00	.1135E+01	.4286E-23
1.10	.1138E+01	.3908E-23
1.20	.1141E+01	.3590E-23
1.30	.1142E+01	.3318E-23
1.40	.1143E+01	.3084E-23
1.50	.1144E+01	.2880E-23
1.60	.1144E+01	.2700E-23
1.70	.1143E+01	.2540E-23
1.80	.1143E+01	.2398E-23
1.90	.1142E+01	.2270E-23
2.00	.1141E+01	.2155E-23
2.10	.1140E+01	.2050E-23
2.20	.1139E+01	.1954E-23
2.30	.1137E+01	.1867E-23
2.40	.1136E+01	.1787E-23
2.50	.1134E+01	.1713E-23
2.60	.1133E+01	.1645E-23
ENERGY	NORMALIZED CROSS SECTION	
.10	.96823662E+00	
.20	.97877150E+00	
.30	.98361602E+00	
.40	.98640398E+00	
.50	.98821811E+00	
.60	.98949447E+00	
.70	.99044257E+00	
.80	.99117554E+00	
.90	.99175986E+00	
1.00	.99223716E+00	
1.10	.99263482E+00	
1.20	.99297162E+00	
1.30	.99326084E+00	
1.40	.99351216E+00	
1.50	.99373277E+00	
1.60	.99392818E+00	
1.70	.99410261E+00	
1.80	.99425941E+00	
1.90	.99440125E+00	
2.00	.99453026E+00	
2.10	.99464820E+00	
2.20	.99475652E+00	
2.30	.99485641E+00	
2.40	.99494888E+00	
2.50	.99503479E+00	
2.60	.99511485E+00	

EFFECTIVE RANGE/SCATTERING LENGTH
 - .11221C1618E+00
 RADIUS POTENTIAL DEPTH
 .1068E-12 .5738E+02
 ENERGY PHASE ANGLE CROSS SECTION,
 L=0 L=0

.10	.8005E+00	.2686E-22
.20	.9412E+00	.1703E-22
.30	.1009E+01	.1245E-22
.40	.1049E+01	.9797E-23
.50	.1075E+01	.8068E-23
.60	.1093E+01	.6852E-23
.70	.1105E+01	.5950E-23
.80	.1115E+01	.5254E-23
.90	.1122E+01	.4702E-23
1.00	.1127E+01	.4252E-23
1.10	.1130E+01	.3879E-23
1.20	.1133E+01	.3564E-23
1.30	.1135E+01	.3296E-23
1.40	.1136E+01	.3064E-23
1.50	.1137E+01	.2861E-23
1.60	.1137E+01	.2683E-23
1.70	.1137E+01	.2525E-23
1.80	.1136E+01	.2384E-23
1.90	.1136E+01	.2257E-23
2.00	.1135E+01	.2143E-23
2.10	.1134E+01	.2039E-23
2.20	.1133E+01	.1944E-23
2.30	.1132E+01	.1857E-23
2.40	.1130E+01	.1778E-23
2.50	.1129E+01	.1704E-23
2.60	.1127E+01	.1636E-23
ENERGY	NORMALIZED CROSS SECTION	
.10	.93747776E+00	
.20	.95781212E+00	
.30	.96730933E+00	
.40	.97281728E+00	
.50	.97641799E+00	
.60	.97895922E+00	
.70	.98085103E+00	
.80	.98231599E+00	
.90	.98348532E+00	
1.00	.98444143E+00	
1.10	.98523866E+00	
1.20	.98591430E+00	
1.30	.98649480E+00	
1.40	.98699944E+00	
1.50	.98744260E+00	
1.60	.98783524E+00	
1.70	.98818582E+00	
1.80	.98850104E+00	
1.90	.98878622E+00	
2.00	.98904565E+00	
2.10	.98928285E+00	
2.20	.98950072E+00	
2.30	.98970165E+00	
2.40	.98988768E+00	
2.50	.99006050E+00	
2.60	.99022157E+00	

EFFECTIVE RANGE/SCATTERING LENGTH
 - .1163660937E+00
 RADIUS
 .1065E-12
 POTENTIAL DEPTH
 .5757E+02
 ENERGY PHASE ANGLE CROSS SECTION,
 L=0 L=0

.10	.7842E+00	.2601E-22
.20	.9264E+00	.1667E-22
.30	.9957E+00	.1224E-22
.40	.1037E+01	.9661E-23
.50	.1064E+01	.7971E-23
.60	.1082E+01	.6778E-23
.70	.1096E+01	.5892E-23
.80	.1106E+01	.5207E-23
.90	.1113E+01	.4662E-23
1.00	.1118E+01	.4218E-23
1.10	.1122E+01	.3850E-23
1.20	.1125E+01	.3539E-23
1.30	.1127E+01	.3273E-23
1.40	.1129E+01	.3044E-23
1.50	.1130E+01	.2843E-23
1.60	.1130E+01	.2667E-23
1.70	.1130E+01	.2510E-23
1.80	.1130E+01	.2370E-23
1.90	.1130E+01	.2244E-23
2.00	.1129E+01	.2131E-23
2.10	.1128E+01	.2028E-23
2.20	.1127E+01	.1934E-23
2.30	.1126E+01	.1848E-23
2.40	.1125E+01	.1769E-23
2.50	.1124E+01	.1696E-23
2.60	.1122E+01	.1628E-23

ENERGY NORMALIZED CROSS SECTION

.10	.90772760E+00
.20	.93714849E+00
.30	.95110169E+00
.40	.95925670E+00
.50	.96461287E+00
.60	.96840489E+00
.70	.97123418E+00
.80	.97342875E+00
.90	.97518273E+00
1.00	.97661832E+00
1.10	.97781634E+00
1.20	.97883232E+00
1.30	.97970572E+00
1.40	.98046532E+00
1.50	.98113263E+00
1.60	.98172405E+00
1.70	.98225227E+00
1.80	.98272732E+00
1.90	.98315716E+00
2.00	.98354827E+00
2.10	.98390590E+00
2.20	.98423442E+00
2.30	.98453743E+00
2.40	.98481798E+00
2.50	.98507864E+00
2.60	.98532158E+00

EFFECTIVE RANGE/SCATTERING LENGTH
 - .1205220256E+00
 RADIUS POTENTIAL DEPTH
 .1062E-12 .5776E+02
 ENERGY PHASE ANGLE CROSS SECTION,
 L=0 L=0

.10	.7684E+00	.2519E-22
.20	.9120E+00	.1630E-22
.30	.9828E+00	.1203E-22
.40	.1025E+01	.9525E-23
.50	.1053E+01	.7873E-23
.60	.1072E+01	.6704E-23
.70	.1086E+01	.5833E-23
.80	.1097E+01	.5159E-23
.90	.1104E+01	.4622E-23
1.00	.1110E+01	.4184E-23
1.10	.1114E+01	.3820E-23
1.20	.1118E+01	.3513E-23
1.30	.1120E+01	.3250E-23
1.40	.1122E+01	.3023E-23
1.50	.1123E+01	.2825E-23
1.60	.1124E+01	.2650E-23
1.70	.1124E+01	.2495E-23
1.80	.1124E+01	.2356E-23
1.90	.1124E+01	.2231E-23
2.00	.1123E+01	.2119E-23
2.10	.1122E+01	.2017E-23
2.20	.1122E+01	.1923E-23
2.30	.1121E+01	.1838E-23
2.40	.1119E+01	.1760E-23
2.50	.1118E+01	.1687E-23
2.60	.1117E+01	.1620E-23
ENERGY	NORMALIZED CROSS SECTION	
.10	.87898331E+00	
.20	.91680363E+00	
.30	.93501300E+00	
.40	.94573795E+00	
.50	.95281525E+00	
.60	.95784165E+00	
.70	.96160045E+00	
.80	.96452096E+00	
.90	.96685819E+00	
1.00	.96877317E+00	
1.10	.97037256E+00	
1.20	.97172985E+00	
1.30	.97289732E+00	
1.40	.97391316E+00	
1.50	.97480592E+00	
1.60	.97559741E+00	
1.70	.97630453E+00	
1.80	.97694060E+00	
1.90	.97751627E+00	
2.00	.97804014E+00	
2.10	.97851924E+00	
2.20	.97895939E+00	
2.30	.97936541E+00	
2.40	.97974136E+00	
2.50	.98009068E+00	
2.60	.98041627E+00	

BIBLIOGRAPHY

1. J.M. Blatt and J. David Jackson, Phys. Rev. 26 18 (1949)
2. C.D. Bowman and W.C. Dickenson, University of California, Lawrence Radiation Laboratory Report No. UCRL - 7859, (1964) (Unpublished).
3. M.J. Moravcsik, Phys. Rev. 136, B 624 (1964).
4. E.Segre, Nuclei and Particles, W.A. Benjamin, Inc., New York (1964)
5. University of California, Lawrence Radiation Laboratory Report No. UCRL 8030 (rev), (1964)
6. Ta-You-Wu and Takashi Ohmura, Quantum Theory of Scattering, Prentice-Hall (1962)
7. W.B. Zeleny, U.S. Naval Postgraduate School, Quantum Mechanics, (1964) (unpublished).

thes0826

Computer investigation of low energy neu



3 2768 001 97400 9

DUDLEY KNOX LIBRARY